








FEATURES:

- Multi function device allowing for system test (5.6K), system or floor drain, and "off" position.
- Integrated Sight Glass
- Angle design for ease of installation in difficult locations
- Rated for 300 psi
- Complies with all requirements of NFPA 13
- UL/FM Listed and Approved







	MATERIAL LIST		
NUMBER	DESCRIPTION	MATERIAL	
1	Body	C37700	
2	Сар	C37700	
3	Seal	PTFE	
4	Ball	C37700	
5	Stem	C37700	
6	O-Ring	NBR	
7	Lever	Steel	
8	Indicator Plate	Steel	
9	Nut	Steel	
10	Plug	C37700	
11	Washer	NBR	
12	Sight Glass	Lexan	
13	Retaining Ring	C37700	

A (NPT)	В	С	D (ref)	Е	F	G
3⁄4"	0.67	4.21	4.72	2.2	4.76	1.81
1"	0.91	4.82	5.31	2.4	4.76	2.17
1¼"	1.18	5.26	5.75	2.83	5.55	2.36
1½"	1.5	5.28	5.67	3.22	6.34	2.56
2"	1.85	6.02	6.54	3.43	6.34	2.83

PROJECT	APPROVAL STAMP
PROJECT:	□ APPROVED
ADDRESS:	□ APPROVED AS NOTED
ENGINEER:	□ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	