


CONTINUOUS THREADED ROD

MODEL LVATR, LVATRSS



DESCRIPTION:

- Size Range: 1/4" through 1-1/2". Stocked in six, ten, and twelve foot lengths. Other even foot lengths can be furnished to order.
- Material: Carbon steel. Available black, galvanized, zinc-plated A307;
 Stainless Steel Type 304 and 316
- Threads: National Coarse (USS)
- Maximum Temperature: Zinc Plated 450°F, Stainless Steel 650°F.
- Approvals: Complies with MSS SP-58
- Ordering: Specify rod diameter, length, finish, and material



DIMENSIONS			
ROD SIZE (in.) A	THREADS PER INCH	MAX LOAD 6500F	WEIGHT PER ft. (lbs.)
1/4	20	240	0.12
3/8	16	730	0.30
1/2	13	1,350	0.53
5/8	11	2,160	0.84
3/4	10	3,230	1.20
7/8	9	4,480	1.70
1	8	5,900	2.30
1-1/4	7	9,500	3.60
1-1/2	6	13,800	5.10

PROJECT	APPROVAL STAMP
PROJECT:	☐ APPROVED
ADDRESS:	☐ APPROVED AS NOTED
ENGINEER:	☐ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	

Revision: 11/2025