



IE28-630T (STRAIGHT BODY)



Product Categories: [Uncategorized](#)

Product Page: <https://www.wilsonandcousins.com/product/ie28-630t/>

Product Summary

6.0" NPT x (2)3.0" NPT - Inline Recessed Brass FDC w. Double Drop Clappers

Product Description

INFORMATION

Wilson and Cousins' **IE28-630T** is a recessed style inline Siamese connection with a 500 GPM inlet capacity and features a single 6.0" (DN150) NPT outlet with two 3.0" (DN80) NPT inlets. The cast brass body can be used as an auxiliary connection to supplement fire protection water supply systems and is rated for working pressures up to 250 psi. This connection, with dual independent self-closing clapper valves, can be concealed inside of a building wall during construction. UL/ULC Approved.

FINISH: Cast Brass

LISTED



Product Attributes

- Dimensions: N/A
- Weight: 8.6 kg

Engineering Specifications

Wilson and Cousins®; **IE28-630T**:

- Inline recessed (flush-mount) cast brass body FDC - 6.0" (DN150) NPT Outlet - 3.0" (DN80) Dual NPT inlet with drop clappers - Each inlet can supply up to 250 GPM - Rated working pressure of 250 psi - UL/ULC Listed

Dimensions

- A: 11.81" (300 mm)
- B: 8.25" (210 mm)
- C: 7.63" (194 mm)
- D: 7.06" (180 mm)



IE28-4T (STRAIGHT BODY)



Product Categories: [Uncategorized](#)

Product Page: <https://www.wilsonandcousins.com/product/ie28-4t/>

Product Summary

4.0" NPT x (2)2.5" NPT - Inline Recessed Brass FDC w. Double Drop Clappers

Product Description

INFORMATION

Wilson and Cousins' **IE28-4T** is a recessed style inline siamese connection with a 500 GPM inlet capacity and features a single 4.0" (DN100) NPT outlet with two 2.5" (DN65) NPT inlets. The cast brass body can be used as an auxiliary connection to supplement fire protection water supply systems and is rated for working pressures up to 250 psi. This connection, with dual independent self-closing clapper valves, can be concealed inside of a building wall during construction. UL/ULC Approved.

FINISH

Cast Brass

LISTED



Product Attributes

- Dimensions: N/A
- Weight: 5.5 kg

Engineering Specifications

Wilson and Cousins's **IE28-4T**:

- Inline recessed (flush-mount) cast brass body FDC - 4.0" (DN100) NPT Outlet - 2.5" (DN65) Dual NPT inlet with drop clappers - Each inlet can supply up to 250 GPM - Rated working pressure of 250 psi - UL/ULC Listed

Dimensions

- A:** 10.56" (268 mm)
- B:** 5.88" (150 mm)
- C:** 7.00" (178 mm)
- D:** 5.06" (128 mm)



IE28-430T (STRAIGHT BODY)



Product Categories: [Uncategorized](#)

Product Page: <https://www.wilsonandcousins.com/product/ie28-430t/>

Product Summary

4.0" NPT x (2)3.0" NPT - Inline Recessed Brass FDC w. Double Drop Clappers

Product Description

INFORMATION

Wilson and Cousins' **IE28-430T** is a recessed style inline siamese connection with a 500 GPM inlet capacity and features a single 4.0" (DN100) NPT outlet with two 3.0" (DN80) NPT inlets. The cast brass body can be used as an auxiliary connection to supplement fire protection water supply systems and is rated for working pressures up to 250 psi. This connection, with dual independent self-closing clapper valves, can be concealed inside of a building wall during construction. UL/ULC Approved.

FINISH

Cast Brass

LISTED



Product Attributes

- Dimensions: N/A
- Weight: 7.3 kg

Engineering Specifications

Wilson and Cousins **IE28-430T**:

- Inline recessed (flush-mount) cast brass body FDC - 4.0" (DN100) NPT Outlet - 3.0" (DN80) Dual NPT inlet with drop clappers - Each inlet can supply up to 250 GPM - Rated working pressure of 250 psi - UL/ULC Listed

Dimensions

- A: 11.81" (300 mm)
- B: 7.25" (184 mm)
- C: 7.63" (194 mm)
- D: 5.19" (131 mm)