

HARD COPPER TUBING

MODEL LVCUHT



DESCRIPTION:

Lansdale's Hard Copper Tube is for use in plumbing, AWWA, and mechanical applications. Available Type K ranging from 1/2" to 3" in diameter, in 20 ft. lengths.

KEY SPECIFICATIONS:

Lansdale's Copper Tube conform to the **NSF/ANSI/CAN 61** Annex G requirements and is manufactured to meet ASTM B88.

INSTALLATION:

Installations shall comply with the latest applicable building codes for the local jurisdiction. For detailed installation instructions, consult the Copper Development Association at copper.org.

REFERENCES:

C12200 NSF/ANSI/CAN 61 Annex G

ASTM B88

ASTM B306 NSF/ANSI/372 99.9% Pure Copper (can be used for potable water) Safe Drinking Water Act (third party certification) Seamless Copper Water and Gas Tube (Type K,L,M)

Seamless Drainage Tube Code (DWV)
Safe Drinking Water (Lead Content)

TYPE K HARD COPPER TUBING				
NPS SIZE (in.)	ACTUAL OD	WALL THICKNESS	WEIGHT 16/FT	Working Pressure (PSI) 140°
1/2	5/8	0.049	0.344	850
3/4	7/8	0.065	0.641	800
1	1-1/8	0.065	0.839	620
1-1/4	1-3/8	0.065	1.037	500
1-1/2	1-5/8	0.072	1.361	470
2	2-1/8	0.083	2.063	410
2-1/2	2-5/8	0.095	2.926	380
3	3-1/8	0.109	4.003	360

PROJECT	APPROVAL STAMP
PROJECT:	☐ APPROVED
ADDRESS:	☐ APPROVED AS NOTED
ENGINEER:	□ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	