

LANSDALE

VALVE & MANUFACTURING

www.LansdaleValve.com

PIPE DOPE

Model LVPD

FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings. FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation or its affiliates.

DESCRIPTION

Lansdale's Lans Seal Pipe Dope is a premium thread sealant with PTFE. It is a non-hardening thread sealant, that is suitable for use on all types of piping used in fire sprinkler, plumbing and industrial applications. It can be used on CPVC and is FBC Compatible. The Lans Seal pipe dope will help prevent leaks by filling voids in the threads and the PTFE offers improved lubricating qualities which achieves improved fitting assembly and sealing.

INSTALLATION

Before applying the Lans Seal pipe dope make sure that all male and female threads are free of any debris and burrs. Apply generously to the male threads and brush the pipe dope into the root of the threads. After the fitting is assembled or, "made on" to the pipe, excess pipe dope should be wiped off. The threading of the fitting and pipe will ensure enough pipe dope remains in the joint. Keep covered when not in use, if any settling occurs, stirring the pipe dope may be necessary.

NEVER USE PIPE DOPE AND TEFLON TAPE TOGETHER

SPECIFICATIONS

- 1 Quart Container
- Greyish/White Paste with no odor
- Stability- Stable under normal storage and handling conditions
- MSDS - <https://www.breccocorp.com/user/products/SDS-Lanseal.pdf>

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	