

PIPE GASKET LUBRICANT

Model LVGCG



DESCRIPTION

Lansdale’s Lans Lube is a vegetable based lubricant that can be used on all applicable gasketed fittings including grooved fittings for fire protection systems, plumbing systems and all couplings utilizing any grade of EPDM gasket. Lans Lube not only helps in the assembly of the grooved joint but also the operation of the system by allowing the gasket to better “seat” when installed. The lubricant is non-staining and does not support bacterial growth, it can be applied from -10 deg F to 150 deg F.



FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings. FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation or its affiliates.

APPLICATION

Lans Lube should be evenly and sparingly applied (especially when used with pre-lubed gaskets). It is best applied by hand after all dirt, burrs, and any other foreign matter is removed from the surfaces. After the Lans Lube is applied the coupling should be assembled following the manufacturers directions.

SPECIFICATIONS

- 1 Quart Container
- Light brown with a dense consistency
- Water soluble
- MSDS - <https://breccocorp.com/user/products/sds-lip-lube.pdf>
- FBC System Compatible

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	