

RISER PAK

MODEL LVRPAK



DESCRIPTION:

- Preassembled for ease of installation
- Can be supplied with test and drain or ball valve as required
- Butterfly valve has built in tamper switch
- Compact design
- Test and drain with optional PRV, available nominal K-Factor: 2.8, 4.2, 5.6, 8.0, 11.2, 14.0 (available on 1-1/4" - 2" size units only), and 25.2 (available on 1-1/2" and 2" size units only)
- All components are UL Listed and FM Approved
- Can be installed both vertically and horizontally. See O&M manual for additional information.

RISER PAK		
SIZE (in.)	OVERALL LENGTH (in.)	OVERALL DEPTH (in.)
1-1/2	23.9	11.5
2	24.3	12
2-1/2	24.8	13.3
3	25.2	14
4	27.2	16
6	30.3	19.5
8	32.3	24.75

PRESSURE DROP EXPRESSED IN EQUIVALENT LENGTHS OF Sch 40 PIPE	
SIZE (in.)	C=120
1-1/2	13.50
2	15.70
2-1/2	15.90
3	18.75
4	18.1
6	19.8
8	18.90

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	