

TOGGLE WING


MODEL LVHTW



FEATURES:

- MATERIAL- Carbon Steel
- FINISH- Electro Galvanized
- Toggle wing can be used with materials such as hollow brick, gypsum board, cement fiber board and wood board
- Suitable for installation of light-weight piping
- Fold up the arm of the toggle wing to insert it into the hole and twist the screw easily
- The arm of toggle wing spreads behind the hollow substrate automatically, and forms a large radius and contact area
- It can be used for a large hollow walls and ceilings

SPECIFICATION (IN)	WING LENGTH	BEARING CAPACITY (LBS)	DRILLING DIAMETER (IN)	SCREW LENGTH
1/4	2.16	154	.71	Screw Length > Wall thickness + 1.18 in
5/16	2.95	264	.87	Screw Length > Wall thickness + 1.58 in
3/8	2.95	440	1.00	Screw Length > Wall thickness + 1.58 in




GYPSUM BOARD



BOARD



CEMENT FIBERBOARD



HOLLOW BRICK

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	