

ZINC FLANGE PACKS (FULLY THREADED)

MODEL LVFPFT



DESCRIPTION:

Flange Packs include everything needed to make-up a flanged assembly. Each kit includes one 1/8" red rubber ring gasket and the correct number of plated hex head bolts and nuts per flange.

SPECIFICATIONS:

- Each kit contains one 1/8" thick red rubber ring gasket meeting ASTM D-1330 CL-125/150 and the following ASTM A307 plated bolts and ASTM A563 GR A hex nuts according to size
- 1/8" thick either Ring or Full Face per ANSI/AWWA C110/A21.10 and ANSI/AWWA C111/A21.11
- Temp. range: Max. 170°F (77°C); Min. -20°F (-29°C)
- Max. working pressure: 150 PSIG

CLASS 150		
SIZE (in.)	NO. OF BOLTS	BOLT SIZE (in.)
4	8	5/8 x 3
6	8	3/4 x 3-1/2
8	8	3/4 x 3-1/2
10	12	7/8 x 4

PROJECT	APPROVAL STAMP
PROJECT:	☐ APPROVED
ADDRESS:	☐ APPROVED AS NOTED
ENGINEER:	☐ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	

Revision: 7/2025